


## SOT-23 Plastic-Encapsulate Transistors

### FEATURES

- Complementary To KTA1505.
- Excellent HFE Linearity.
- Low noise.
- NPN Silicon Epitaxial Planar Transistor
- General purpose application, switching application.

### MECHANICAL DATA

- Case style: SOT-23 molded plastic
- Mounting position: any



## MAXIMUM RATINGS AND CHARACTERISTICS

@ 25°C Ambient Temperature (unless otherwise noted)

Symbol	Parameter	Value	Units
$V_{CBO}$	Collector-Base Voltage	35	V
$V_{CEO}$	Collector-Emitter Voltage	30	V
$V_{EBO}$	Emitter-Base Voltage	5	V
$I_C$	Collector Current -Continuous	500	mA
$P_C$	Collector Power Dissipation	150	mW
$T_j, T_{stg}$	Junction and Storage Temperature	-55 to +150	°C

### PACKAGE INFORMATION

Device	Package	Shipping
KTC3876	SOT-23	3000/Tape&Reel

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=100\mu A, I_E=0$	35			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=1mA, I_B=0$	30			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=100\mu A, I_C=0$	5			V
Collector cut-off current	$I_{CBO}$	$V_{CB}=35V, I_E=0$			0.1	$\mu A$
Emitter cut-off current	$I_{EBO}$	$V_{EB}=5V, I_C=0$			0.1	$\mu A$
DC current gain	$h_{FE}$	$V_{CE}=1V, I_C=100mA$ $V_{CE}=6V, I_C=400mA$	70 25		400	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=100mA, I_B=10mA$		0.1	0.25	V
Base-emitter voltage	$V_{BE}$	$V_{CE}=1V, I_C=100mA$		0.8	1.0	V
Transition frequency	$f_T$	$V_{CE}=6V, I_C=20mA$		300		MHz
Collector output capacitance	$C_{ob}$	$V_{CB}=6V, I_E=0, f=1MHz$		7		pF

### CLASSIFICATION OF $h_{FE}$

Rank	O	Y	G
Range	70-140	120-240	200-400
Marking	WO	WY	WG